

INDASH by PANAVISE®

I-75103-597

Page 1 of 1

MOUNTING LOCATION:

Right side of radio

CELL PHONE & MEDIA MOUNT

INSTALLATION INSTRUCTIONS

TOOLS REQUIRED:

5/64 Allen wrench drill
Drill & #36 drill bit
Phillips screwdriver
Flat screwdriver

PART#: **75103-597**
MFG: **BMW**
MODELS & YEARS: **318i 1996-1998**
323i 1998, 328i 1996-1998, M3 1996-2000

** ADVISEMENT **

Read instructions completely prior to starting installation. All InDash Mounts are designed so that after installation, phone is facing normal driver position for left-hand drive vehicles. This mount is not designed to be used in foreign countries with right-hand drive vehicles. Use extreme care when working around the plastic components on the dash. Excess force, can cause breakage of the plastic components.

HARDWARE INCLUDED:

(1) A - #8X9/16 Needle Point Screw

- STEP #1 Remove the radio by opening two tabs located on both sides of the radio. Using the 5/64 Allen wrench on the set screws located under the tabs, turn counter clockwise until the radio is released. Carefully pull radio out and set it on the console.
- STEP #2 Insert the Indash Mount between the right side of the radio cavity (plastic) and the dash (vinyl side). Push the Indash Mount in until the bend rests on the outside step of the radio cavity. Once the mount is pushed in, locate a hole that is about 1 inch in from the step where the radio rests inside the radio cavity. Once you have located this hole, with #36 drill bit, drill a pilot hole thru the hole on the Indash Mount. Install the provided screw on the pilot hole. This will secure the Indash in place.
- STEP #3 Push radio back into place and lock it securely by tightening the set screws with the 5/64 Allen wrench.
- STEP #4 Attach phone holder to Indash Mount.

INSTALLATION IS NOW COMPLETE. ENJOY YOUR NEW PANAVISE INDASH MOUNT.



The unit pictured is our handmade prototype model, not a production part. **This photo is for location reference only.**



09-03-04