



MOBILE DASH MOUNT E46 INSTALLATION INSTRUCTIONS

Prior to installation:

Read instructions completely before installation.

Use care when removing any plastic pieces from the vehicles dash. Unnecessary force can cause plastic pieces to crack or break.

TOOLS REQUIRED FOR INSTALLATION: Flat head and Philips screwdriver, trim tool (if available), 10mm socket driver or 10mm wrench.



- 1) Locate the trim piece that is below the passenger side airbag. Remove this trim carefully prying toward you to release the first clip starting from the right side, pushing down on the dash to reveal the first clip. Do this using the trim tool or flat head screwdriver if you do not have a trim tool.



- 2) Continue working the trim piece loose over to the right releasing the total of 4 clips. Sometime the orange clip holders will come out. In this case simple remove the holder from the clip and replace into dash.



- 3) Locate and remove the 10mm hex head nut to the right of the radio with the 10mm socket driver or wrench.



- 4) Place the bracket over the stud. Replace the 10mm nut and tighten. Before you completely tighten the bracket down make sure the bracket is as low as it can be as to avoid obstructing the path of the trim once it is reinstalled. Failing to do this could result in the trim piece not sitting properly.



- 5) Carefully reinstall the dash in reverse order securing all the trim clips.



- 6) Install the mounting device onto the bracket using the hardware that came with your particular holder.

Check compatibility of product with vehicle manufacturer before installation. Bimbian or any of it's subsidiaries, employees, owners, operators, or sub-contractors will not be liable for your use or inability to use this product or any problems arising from your use of this product whether directly or indirectly caused by the use of this product.



MOBILE DASH MOUNT X5 INSTALLATION INSTRUCTIONS

Prior to installation:

Read instructions completely before installation.

Use care when removing any plastic pieces from the vehicles dash. Unnecessary force can cause plastic pieces to crack or break.

TOOLS REQUIRED FOR INSTALLATION: Flat head and Philips screwdriver, trim tool (if available), 5/64" drill bit and hand drill.



- 1) Locate the trim piece that is below the passenger side airbag. Remove this trim carefully prying toward you to release the first clip. Do this using the trim tool or flat head screwdriver if you do not have a trim tool. Continue working the trim piece loose over to the right releasing the total of 3 clips. Sometime the orange clip holders will come out. In this case simple remove the holder from the clip and replace into dash.to socket making sure it sits firmly between the socket clips.

- 2) Place the bracket just under the left clip hole. Use the holes in the bracket as a guide to mark two pilot holes. Use the 5/16" drill bit and drill two pilot holes. Mount bracket with screws provided using a philips screwdriver.



- 3) Carefully reinstall the dash in reverse order securing all the trim clips. Install the mounting device onto the bracket using the hardware that came with your particular holder.

Check compatibility of product with vehicle manufacturer before installation. Bimbian or any of it's subsidiaries, employees, owners, operators, or sub-contractors will not be liable for your use or inability to use this product or any problems arising from your use of this product whether directly or indirectly caused by the use of this product.